

ADAM-6521 / ST (New)

**Industrial Switch with
4 10/100 Mbps Ethernet
Ports & 1 Multi-mode ST
Type Fiber Optic Port**

NEW



Features

- Provides 4 x 10/100 Mbps Ethernet ports with RJ-45 connector
- Provides 1 x 100 Mbps multi/single-mode fiber port with ST connector
- Supports full/half duplex flow control
- Supports Integrated Loop-up engine
- Supports MDI/MDI-X auto crossover
- Provides broadcast storm protection
- Supports +10 ~ 30 V_{DC} voltage power input
- Provides surge protection (EFT) 3,000 V_{DC} for power line
- Supports 4,000 V_{DC} Ethernet ESD protection
- Provides flexible mounting: DIN-rail, panel, piggyback
- Supports operating temperatures from -10 ~ 65° C

Introduction

ADAM-6521/ST is an industrial-grade Ethernet switch with a fiber optic port that makes it possible to expand industrial networks fast and cost-effectively. ADAM-6521/ST has 1 fiber port and 4-RJ-45 ports. With fiber optics, you can prevent noise interfering with your system and implement transmission distances up to 15 km. ADAM-6521/ST supports a wide voltage range of +10 ~ 30 V_{DC} over the terminal block, and 3,000 V_{DC} surge protection (EFT) to protect it from being damaged by over-voltage. A wide operating temperature range from -10 to 65° C (14 ~ 149° F), makes it functional in harsh operating environments.

Six inclusive LED indicators make troubleshooting easier. Each port has a pair of LEDs that indicate link status and transmission speed. This function conveniently informs users of any collisions, the link status, power failure and data receipts for immediate on-site diagnostics.

Specifications

Communications

- **Standard** IEEE 802.3, 802.3u, 802.3x
- **LAN** 10/100Base-T, 100Base-FX
- **Transmission Distance** Ethernet: 100 m
Fiber: 2km
- **Transmission Speed** Ethernet : up to 100 Mbps
Fiber : 100 Mbps

Interface

- **Connectors** 1 x ST type fiber connector
- **LED Indicators** Power, Link (100Base-FX), 100/10M (Ethernet)

Power

- **Power Connectors** 2-pin removable screw terminal
- **Power Consumption** Max.3W
- **Power Input** Unregulated 10 ~ 30 V_{DC}

Mechanism

- **Dimensions(W x H x D)** 70 x 112 x 27 mm
- **Enclosure** IP30, ABS+PC with solid mounting hardware
- **Mounting** DIN 35 rail, stack, wall

Protection

- **ESD Protection** 4,000 V_{DC} (Ethernet)
- **Surge (EFT) Protection** 3,000 V_{DC} (Power)

Environment

- **Operating Temperature** -10 ~ 65° C (14 ~ 149° F)
stack : -10 ~ 60° C (14 ~ 140° F)
- **Storage Temperature** -20 ~ 80° C (-4 ~ 176° F)
- **Operating Humidity** 20-95% (non-condensing)
- **Storage Humidity** 0-95% (non-condensing)
- **MTBF** 1,150,000 hrs

Certifications

- **Safety** UL 60950-1, CAN/CSA-C22.2 No.60950
- **EMC** U.S.A.: FCC Part 15 CISPR 22
EU: EN55011
EN55022 Class A,
EN61000-3-2/3
EN55024
IEC61000-4-2/3/4/5/6/8/11

Ordering Information

- **ADAM-6521** Industrial Switch with 4 10/100 Mbps Ethernet Ports & 1 Multi-mode SC Type Fiber Optic Port
- **ADAM-6521/ST** Industrial Switch with 4 10/100 Mbps Ethernet Ports & 1 Multi-mode ST Type Fiber Optic Port
- **ADAM-6521S** Industrial Switch with 4 10/100 Mbps Ethernet Ports & 1 Single-mode SC Type Fiber Optic Port